



Image Series Specifications



Available in Dark Cherry or
Black Ash.

Image Series



	Image T6 Tower	Image T5 Tower	Image B6 Bookshelf	Image B5 Bookshelf	Image B4 Compact Bookshelf / Surround	Image C5 Centre	Image C4 Centre	Image S5 Surround
Frequency Response (Anechoic Chamber)								
On Axis @ 0°±3dB	32-23,000Hz	35-23,000Hz	45-23,000Hz	50-23,000Hz	60-23,000Hz	50-23,000Hz	60-23,000Hz	68-23,000Hz
On Axis @ 0°±1 1/2dB	45-20,000Hz	48-20,000Hz	59-20,000Hz	70-20,000Hz	70-20,000Hz	65-20,000Hz	70-20,000Hz	70-20,000Hz
Off Axis @ 30°±1 1/2dB	45-10,000Hz	48-10,000Hz	59-10,000Hz	70-10,000Hz	70-10,000Hz	65-10,000Hz	70-10,000Hz	70-10,000Hz
LF Cutoff -10dB	28Hz	30Hz	40Hz	50Hz	55Hz	45Hz	55Hz	58Hz
Sensitivity (1W (2.83V) @ 1M, IEC-Filtered pink noise, C-weighted)								
Anechoic Chamber	89dB	88dB	89dB	87dB	85dB	88dB	86dB	87dB
Listening Room	91dB	90dB	90dB	89dB	87dB	90dB	88dB	89dB
Impedance								
Nominal	8 Ohms	8 Ohms	8 Ohms	8 Ohms	8 Ohms	8 Ohms	8 Ohms	8 Ohms
Minimum	4 Ohms	4 Ohms	4 Ohms	4 Ohms	4 Ohms	4 Ohms	4 Ohms	4 Ohms
Input Power (RMS, Clipping <10% Time)								
Recommended Program	20 - 200 Watts 200 Watts	20 - 200 Watts 200 Watts	20 - 150 Watts 150 Watts	20 - 150 Watts 150 Watts	10 - 80 Watts 60 Watts	20 - 150 Watts 150 Watts	10 - 80 Watts 60 Watts	20 - 150 Watts 150 Watts
Acoustic Design								
Tweeter (Nominal)	1" (25mm) Titanium Dome with Ferrofluid Neodymium Magnet	1" (25mm) Titanium Dome with Ferrofluid Neodymium Magnet	1" (25mm) Titanium Dome with Ferrofluid Neodymium Magnet	1" (25mm) Titanium Dome with Ferrofluid Neodymium Magnet	1" (25mm) Titanium Dome with Ferrofluid Neodymium Magnet	1" (25mm) Titanium Dome with Ferrofluid Neodymium Magnet	1" (25mm) Titanium Dome with Ferrofluid Neodymium Magnet	2 x 1" (25mm) Titanium Dome with Ferrofluid Neodymium Magnet
Midrange (Nominal)	5 1/4" (133mm) Clay/Ceramic reinforced Polypropylene Cone Rubber Surround							
Woofer (Nominal)	2 x 6 1/2" (165mm) Clay/Ceramic reinforced Polypropylene Cone Rubber Surround	2 x 5 1/4" (133mm) Clay/Ceramic reinforced Polypropylene Cone Rubber Surround	6 1/2" (165mm) Clay/Ceramic reinforced Polypropylene Cone Rubber Surround	5 1/4" (133mm) Clay/Ceramic reinforced Polypropylene Cone Rubber Surround	4" (102mm) Clay/Ceramic reinforced Polypropylene Cone Rubber Surround	2 x 5 1/4" (133mm) Clay/Ceramic reinforced Polypropylene Cone Rubber Surround	2 x 4" (102mm) Clay/Ceramic reinforced Polypropylene Cone Rubber Surround	2 x 5 1/4" (133mm) Clay/Ceramic reinforced Polypropylene Cone Rubber Surround
Crossover	2,200Hz, LR4, 500Hz, B3	1,800Hz, LR4, 800Hz	1,800Hz, LR4	1,800Hz, LR4	2,200Hz, LR4	1,800Hz, LR4	2,200Hz, LR4	1,800Hz, LR4
Internal Volume	1.93 cu ft (54.7L)	1.42 cu ft (40.2L)	0.48 cu ft (13.6L)	0.32 cu ft (9.1L)	0.1 cu ft (2.8L)	0.58 cu ft (16.4L)	0.21 cu ft (6.0L)	0.23 cu ft (6.5L)
Design Type	Sealed Mid-Range Chamber Dual Port Bass Reflex	Bass Reflex	Bass Reflex	Bass Reflex	Bass Reflex	Bass Reflex	Bass Reflex	Sealed Bipole
Size (W x H x D) (Gross Dimensions)								
	9 1/8 x 40 5/8 x 15" ** 231 x 1031 x 380mm Spikes add 1" (25mm)	8 1/2 x 36 7/8 x 12 7/8" ** 214 x 936 x 325mm Spikes add 1" (25mm)	7 7/8 x 14 1/8 x 10 5/8" ** 198 x 357 x 268mm	7 1/8 x 12 5/8 x 9 5/8" ** 181 x 318 x 242mm	5 1/4 x 9 1/4 x 6 5/8" ** 133 x 232 x 168mm	19 1/2 x 7 1/8 x 10 1/2" ** 495 x 181 x 265mm	14 1/4 x 5 3/8 x 7 1/2" ** 362 x 134 x 190mm	12 x 11 3/4 x 7 1/8" ** 302 x 298 x 180mm
Weight								
Net	48.5lb (22kg)/each	36.6lb (16.6kg)/each	14.2lb (6.5kg)/each	11.3lb (5.1kg)/each	5.8lb (2.6kg)/each	19.1lb (8.7kg)/each	8.7lb (4kg)/each	13.3lb (6kg)/each
Shipping	58.5lb (26.6kg)/each	44.4lb (20.2kg)/each	31.4lb (14.3kg)/pair	25.6lb (11.6kg)/pair	13.3lb (6kg)/pair	21.7lb (9.9kg)/each	10.1lb (4.6kg)/each	31.2lb (14.2kg)/pair
Finish								
	Black Ash or Dark Cherry	Black Ash or Dark Cherry	Black Ash or Dark Cherry	Black Ash or Dark Cherry	Black Ash or Dark Cherry	Black Ash or Dark Cherry	Black Ash or Dark Cherry	Black Ash or Dark Cherry

** Non-metric measurements are approximate.

All specifications are subject to change without notice. Non-metric measurements are approximate. PSB Speakers will not assume any liability for errors in this brochure which may result in errors being made by retailers, custom installers, cabinet makers or other end users based on information contained in this document. PSB Speakers reserves the right to change specifications or features without notice. © 2012 PSB Speakers, a division of Lenbrook Industries Limited. PSB is a registered trademark of Lenbrook Industries Limited. All rights reserved. No part of this publication may be reproduced, stored or transmitted in any form whatsoever without the written permission of PSB Speakers. 12-019 Printed September 2012.